




MODEL: AMC48DF


48" MERCURY DUAL FUEL RANGE



The AGA Mercury range is known for its bold design, contemporary details, zero-clearance facade and mod style cooking controls. It is truly a statement piece in any luxury kitchen.

Designed and built in the UK, this range is a technical masterpiece, the embodiment of exquisite quality and stylish, thoughtful design. Available in 16 sophisticated finish options, The AGA Mercury range is the perfect match for any mood or lifestyle.





Oven Dimensions: 18 1/2" W x 16" D x 16" H

SPECIFICATIONS

- · Electrical: 240 V 60 Hz
- · Electric Rating: 240V (2 Wire + N + Grd), 60Hz, 7.4 kW
- · Gas: 1/2" NPT at rear right-hand side
- · Oven Ratings:

Fan element (x2): 2.5 kW Top element (x2): 1.2 kW Browning element (x2): 1.15 kW Bottom element (x2): 1.0 kW

- Product Dimensions: 47 % W x 28 5/32" D x 37 3/16" H
- · Shipping weight (lbs): 390 lbs (includes range, crate & pallet)

WARRANTY

· 2 Year Warranty on parts and labor with exception of cosmetic parts & lightbulbs

FINISHES

NOTE: Colors not in stock could have a 4-12 week lead time (check for availability).

Ranges manufactured using Soho colors are only available with stainless steel fascia.

CLASSIC COLOR COLLECTION



Salcombe Blue (0693)

OPTIONAL KNOB FINISH

Fawn (0688)

NOTE: The AGA Mercury ships standard with Stainless Steel Knobs, but also has a Black finish option available as an after-market purchase.

Piccadilly Red (0667)





Cranberry (0658)











48" MERCURY DUAL FUEL RANGE

5 BURNER COOKTOP



7 MULTIFUNCTION COOKING MODES



FEATURES

- 9 Hi-Fi Style Infinite Controls turn with stereo-like grace
- Powerful 8-pass, 2300 watt Broiling Oven ready in 5 minutes
- · Glide-out Broiler System with adjustable heights and extendable gliding tray spacious enough to cook six 6-oz steaks at once
- 5 sealed brass burners; one 17,000 BTU, three 12,000 BTU, one 6,000 BTU, with continuous cast iron grates easily slide pots and pans from burner to burner without spilling. All burners designed with thermocouple safety mechanism.
- 6 interlocking enamel finish cast iron grates x
 LP Conversion Kit included
- One extra-large 7-Mode Multifunction Convection Oven, one true European Convection Oven, Fan-Assisted Baking, Browning, Thaw-to-Serve, Convection Broiling, and Warming
- Over 6 cubic feet of oven space amongst 3 separate ovens maximize utility and reduce energy consumption
- The multifunction oven features 3 heavy-duty stainless steel shelves including a removable Telescopic shelf, while the second oven features 2 heavy-duty stainless steel shelves
- Easy clean technology with black vitreous enamel interior



48" MERCURY DUAL FUEL RANGE

General Properties	
Oven Capacity	6 cu. ft.
Cooking Mode Main Cavity - Right side	Convection Bake 2.8 cu. ft.
	(17" W x 14" D x 14 ½" H*)
Cooking Mode Second Cavity – Left side	Multi-function Oven with 7 Cooking Modes
	2.8 cu. ft.
	(17" W x 14" D x 14 ½" H*)
Cooking Mode Third Cavity - Broiler	Dual-element with 8-pass 2,300W 0 .5 cu. ft.
Cleaning Type	EasyClean™ Enamel
Controls	Knobs on fascia
Sealed Burners	Yes
Oven Performance	
Main Cavity - Right side	2,500W
Second Cavity – Left side	2,500W
Third Cavity - Broiler	2,300W
Broiler Type	8 Pass Radiant Heat
Cooktop Performance	
Cooktop Dimensions	47" \A/ \ 211/ " D
DESTRUCTION OF THE PROPERTY OF	43" W x 21 ½" D
Number of Brass Burners	43 W X 21 7 ₂ D
Number of Brass Burners	5
Number of Brass Burners Power of Left Front Burner	5 12,000 BTU High; 2,400 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU Electrical Details	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low 12,000 BTU High; 2,400 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU Electrical Details Circuit Breaker (A)	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low 12,000 BTU High; 2,400 BTU Low
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU Electrical Details Circuit Breaker (A) Volts (V)	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low 12,000 BTU High; 2,400 BTU Low 40A 240V
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU Electrical Details Circuit Breaker (A) Volts (V) Frequency (Hz)	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low 12,000 BTU High; 2,400 BTU Low 40A 240V 60Hz
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU Electrical Details Circuit Breaker (A) Volts (V) Frequency (Hz) Plug Type	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low 12,000 BTU High; 2,400 BTU Low 40A 240V 60Hz 4 Wire
Number of Brass Burners Power of Left Front Burner Power of Back Left Burner BTU Power of Center Burner BTU Power of Front Right Burner BTU Power of Back Right Burner BTU Electrical Details Circuit Breaker (A) Volts (V) Frequency (Hz) Plug Type Power Cord Length	5 12,000 BTU High; 2,400 BTU Low 12,000 BTU High; 2,400 BTU Low 17,000 BTU High; 3,400 BTU Low 6,000 BTU High; 1,200 BTU Low 12,000 BTU High; 2,400 BTU Low 40A 240V 60Hz 4 Wire 48" Electric Ovens and

