## accuc@ld

# ARG3PV456



34" x 18.5" x 19" (H x W x D)

Performance series Pharma-Vac 3 cu.ft. counter height glass door all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

### **Highlights:**

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

#### **Product Features:**

Certified to NSF/ANSI 456 Vaccine Storage Standard	Certified to NSF/ANSI 456 Vaccine Storage Standard
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support

	meeting CDC/VFC guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Certificate of calibration included	2-year calibration certificate included for your records
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup



# accuc@ld

### **ARG3PV456 Specifications:**

Overview				
Height of Cabinet	34.0" (86 cm)			
Width	18.5" (47 cm)			
Width with Door Open	19.0" (48 cm)			
Depth	19.0" (48 cm)			
Depth with Handle	20.75" (53 cm)			
Depth with door at 90°	36.0" (91 cm)			
Capacity	3.0 cu.ft. (85 L)			
Defrost Type	Automatic			
Door	Glass			
Cabinet	White			
US Electrical Safety	ETL			
Canadian Electrical Safety	ETL-C			
Sanitation	ETL-S to NSF 456			
Amps	0.6			
Voltage/Frequency	115 V AC/60 Hz			
Weight	87.0 lbs. (39 kg)			
Parts & Labor Warranty	2 Years			
Compressor Warranty	5 Years			
UPC	761101090627			
Refrigerator Features				
Door Swing	RHD			
Reversible	Factory Reversible			
Shelf Type	Wire			
Shelf Qty	4			
Adjustable Shelves	Yes			
Thermostat Type	Digital			
Fan Type	Interior			
Refrigerant Type	R600a			
Refrigerant Amount	1.06oz.			
Interior Light	Yes			
Temperature Range	2 to 8°C			
Sound Level	37.6 dB			
Dimensions				
Interior Height	28.38" (72 cm)			
<del></del>	45.05" (00)			
Interior Width	15.25" (39 cm)			
Interior Width Interior Depth	15.25" (39 cm) 11.75" (30 cm)			

Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	3.75" (10 cm)





