## accucold

# ARS1MLDL2B



#### **Product Features:**

#### Purpose-built design Designed and purpose-built to meet the demanding needs of scientific, life science, laboratory, and medical cold storage applications +/-1°C Variation The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period Antimicrobial silver ion-coated handle Powder-coated handle with naturally occurring silver ions to help reduce germ spread Adjustable temperature Intuitive controls let you adjust the interior temperature between +2 to +10°C Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with Digital data logger (DDL) included user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our webiste Temperature alarm Visual and audible alarms alert if the interior temperature rises or falls out of set range Remote alarm contacts Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup defrost

Accessory torvision, FELIX STORCH, INC. | IS to stude a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893 Isorepresented an analysis of the start of t

#### 21.5" x 17.5" x 19.75" (H x W x D)

Performance series Med-Lab 1 cu.ft. compact allrefrigerator for laboratory storage with factory-installed data logger, antimicrobial silver-ion handle, and hospital grade cord with 'green dot' plug

#### **Highlights:**

NIST calibrated DDL included for accurate temperature logging

Intelligent microprocessor digital temperature controller

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

## accucold

### **ARS1MLDL2B Specifications:**

Overview	
Height of Cabinet	21.5" (55 cm)
Width	17.5" (44 cm)
Width with Door Open	18.0" (46 cm)
Depth	19.75" (50 cm)
Depth with Handle	21.5" (55 cm)
Depth with door at 90°	36.0" (91 cm)
Capacity	1.0 cu.ft. (28 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	63.0 lbs. (29 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101065809
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.71oz.
Interior Light	Yes
Temperature Range	2 to 10°C
Sound Level	42 dB
Dimensions	
Interior Height	15.75" (40 cm)
Interior Width	14.0" (36 cm)
Interior Depth	8.0" (20 cm)

