accuc@ld

ARS1PVDL2B



21.5" x 17.5" x 19.75" (H x W x D)

Performance series Pharma-Vac 1 cu.ft. compact allrefrigerator for vaccine storage with factory-installed data logger, antimicrobial silver-ion handle, and hospital grade cord with 'green dot' plug

Highlights:

NIST calibrated DDL included for accurate temperature logging

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Digital data logger (DDL) included	Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our webiste
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

accuc@ld

ARS1PVDL2B Specifications:

Overview	
Height of Cabinet	21.5" (55 cm)
Width	17.5" (44 cm)
Width with Door Open	18.0" (46 cm)
Depth	19.75" (50 cm)
Depth with Handle	21.5" (55 cm)
Depth with door at 90°	36.0" (91 cm)
Capacity	1.0 cu.ft. (28 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	63.0 lbs. (29 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101065687
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Chalf Time	
Shelf Type	Wire
Shelf Type Shelf Qty	
	Wire
Shelf Qty	Wire 3
Shelf Qty Adjustable Shelves	Wire 3 Yes
Shelf Qty Adjustable Shelves Thermostat Type	Wire 3 Yes Digital
Shelf Qty Adjustable Shelves Thermostat Type Fan Type	Wire 3 Yes Digital Interior
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type	Wire 3 Yes Digital Interior R600a
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Wire 3 Yes Digital Interior R600a 0.71oz.
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light	Wire 3 Yes Digital Interior R600a 0.71oz. Yes
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range	Wire 3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level	Wire 3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level Dimensions	Wire 3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C 42 dB
Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level Dimensions Interior Height	Wire 3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C 42 dB

