accucold

ARS62PVBIADA



31.75" x 23.38" x 25" (H x W x D)

Performance series Pharma-Vac 6 cu.ft. ADA height solid door commercial all-refrigerator for the display and refrigeration of vaccines; designed for recessed or freestanding installation

Highlights:

Sized just under 32" high to fit under lower ADA compliant counters

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines	
ADA Compliant	Just under 32" tall designed to fit under ADA compliant counters	
Recessed or freestanding use	Versatile design allows recessed installation under counters or freestanding use	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Commercial design	Meets UL-471 commercial standards	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2°C to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



accuceld

ARS62PVBIADA Specifications:

Overview	
Height of Cabinet	31.75" (81 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Depth	25.0" (64 cm)
Depth with Handle	26.75" (68 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	6.0 cu.ft. (170 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.75
Voltage/Frequency	115 V AC/60 Hz
Weight	125.0 lbs. (57 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101075310
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	
•	Yes
•	Yes Digital
Thermostat Type Fan Type	
Thermostat Type	Digital
Thermostat Type Fan Type	Digital
Thermostat Type Fan Type Refrigerant Type	Digital Interior R600a
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Digital Interior R600a 1.66oz.
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI	Digital Interior R600a 1.66oz. 280.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Digital Interior R600a 1.66oz. 280.0 90.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light	Digital Interior R600a 1.66oz. 280.0 90.0 Yes
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Temperature Range	Digital Interior R600a 1.66oz. 280.0 90.0 Yes 2°C to 8°C
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Temperature Range Sound Level	Digital Interior R600a 1.66oz. 280.0 90.0 Yes 2°C to 8°C
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Temperature Range Sound Level Dimensions	Digital Interior R600a 1.66oz. 280.0 90.0 Yes 2°C to 8°C 34.8 dB
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Temperature Range Sound Level Dimensions Interior Height	Digital Interior R600a 1.66oz. 280.0 90.0 90.0 Yes 2°C to 8°C 34.8 dB 24.5" (62 cm)

Compressor Step Height	6.5" (17 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.0" (13 cm)





