

SBC58BLBIADAIFCFTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap cold brew coffee dispenser with panel-ready door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Dual tap commercial grade tap kit includes everything you need to serve flat cold brew coffee on draft

Commercially listed to NSF-7 standards

Product Features:

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Complete dual tap cold brew coffee kit	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Panel-ready door	Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	
Automatic defrost	No-frost operation for minimum user maintenance	
User-reversible door	Unit ships with a right hand door swing. For a left hand version, add option LHD upon order	
Stainless steel drip tray SUMMIT APPLIANCE DIVISION FELLY STOR	Removable two-piece drip tray included for added convenience	





SBC58BLBIADAIFCFTWIN Specifications:

Nominal Height	32.0" (81 cm)
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.75" (58 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101069661
	701101009001
Kegerator	701101009001
Kegerator Door Swing	RHD
-	
Door Swing	RHD
Door Swing Reversible	RHD Factory Reversible
Door Swing Reversible Tap Kit	RHD Factory Reversible Yes
Door Swing Reversible Tap Kit Height with Tap	RHD Factory Reversible Yes 47.5" (121 cm)
Door Swing Reversible Tap Kit Height with Tap Number of Taps	RHD Factory Reversible Yes 47.5" (121 cm) 2
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type Interior Light	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial Yes
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type Interior Light Fan Type	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial Yes Exterior
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type Interior Light Fan Type Refrigerant	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial Yes Exterior R600a
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial Yes Exterior R600a 0.64 oz.
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial Yes Exterior R600a 0.64 oz. 180.0
Door Swing Reversible Tap Kit Height with Tap Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI	RHD Factory Reversible Yes 47.5" (121 cm) 2 Dial Yes Exterior R600a 0.64 oz. 180.0

Compressor Step Height	6.5" (17 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF



