

# **BIM44GCSS**



#### 33" x 14.5" x 23.25" (H x W x D)

15" wide 50 lb. built-in undercounter commercially listed clear icemaker with automatic defrost, internal pump, and complete stainless steel exterior

#### **Highlights:**

Commercially approved to NSF-12 standards

**Commercial ENERGY STAR certification** 

Produces up to 50 lbs. of clear ice cubes in a day cycle with a 25 lb. storage capacity

## **Product Features:**

Commercially approved	ETL-S listed to NSF-12 commercial standards	
Built-in capable	Make the best use of space by installing your icemaker under the counter	
50 lb. production capacity	Can make up to 50 lbs. of clear ice cubes in a day cycle and store up to 25 lbs. per day (Note: ice is produced in sheets and can easily be broken into cubes using the provided scoop.)	
ENERGY STAR certified commercial performance	Efficient performance saves on energy use and costs	
Built-in pump	Internal pump affords more flexibility in placing the unit	
Automatic defrost	Reduced maintenance with auto defrost system	
Clear ice cube production	Produces 7/8" x 7/8" x 7/8" clear ice cubes	
Touch control panel	Provides easy operation of the unit with indicator lights for each stage of the production process	
Reversible stainless steel door	User-reversible door swing for flexible placement	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 $\checkmark$ 





### **BIM44GCSS Specifications:**

Level Legs

Overview	
Nominal Height	33.0" (84 cm)
Height of Cabinet	33.0" (84 cm)
Nominal Width	15.0" (38 cm)
Width	14.5" (37 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.25" (59 cm)
Depth with Handle	25.25" (64 cm)
Depth with door at 90°	36.75" (93 cm)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	4.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101067759
Icemaker	
Door Swing	LHD
Reversible	Yes
Drain Required	Yes
Daily Ice Production	50.0 lbs. (23 kg)
Ice Storage Capacity	25.0 lbs. (11 kg)
Ice Shape	Cube
Size of Cube	7/8" x 7/8" x 7/8"
Number of Ice Cube Sizes	1
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	3.88 oz.
High Side PSI	350.0
Low Side PSI	130.0
Interior Height	18.5" (47 cm)
Interior Width	12.0" (30 cm)
Interior Depth	16.0" (41 cm)



