



BSP251610

1 x STS tray-GN2/3-punched-40 mm deep
 1 x STS tray-GN2/3-unpunched-40 mm deep
 1 x grid
 1 x pluggable meat probe

GN114130:
 GN insert unperf, st. steel, GN1/3, 40mm

GN114230:
 GN insert unperf, st. steel, GN2/3, 40mm

GN124130:
 GN insert perf, st. steel, GN1/3, 40mm

GN124230:
 GN insert perf, st. steel, GN2/3, 40mm

GN144130:
 GN insert 1/3 unperf, non-stick, 40mm

GN144230:
 GN insert 2/3 unperf, non-stick, 40mm

GN154130:
 GN insert 1/3 perf, non-stick, 40mm

GN154230:
 GN insert 2/3 perf, non-stick, 40mm

GN340230:
 Gastronorm roaster GN 2/3

GN410130:
 GN lid stainless steel 1/3

GN410230:
 GN lid stainless steel 2/3

GR220046:
 Grid for steam oven

Combi-steam oven 200 series
24", Door Hinge: Left, Gaggenau Metallic
BSP251610

- Flush installation
- Water tank
- Convection 85°F to 450°F can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
- TFT touch display
- Steaming without pressure
- Flush installation

Water tank
 Convection 85°F to 450°F can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
 TFT touch display
 Steaming without pressure
 Electronic temperature control from 30 °C to 230 °C
 Removable meat probe
 Net volume (42 litres)

Cooking modes
 Convection + 100 % humidity.
 Convection + 80 % humidity. Convection + 60 % humidity. Convection + 30 % humidity. Convection + 0 % humidity. Dough proofing. Defrosting. Regenerating. Low temperature cooking.

Operation
 Rotary knob and TFT touch display operation.
 Clear text display in 44 languages.
 Option to save 50 individual recipes (incl. core temperature probe)
 Information key with use indicators.
 Side-opening door opens up to 110° angle.

Features
 Removable 1.3 litre water tank.
 Water level warning.
 Meat probe with automatic shut-off function.
 Actual temperature display.
 Timer functions: cooking time, switch-off time, short-term timer, stopwatch.
 Automatic boiling point detection.
 48 W halogen light on the side.
 Hygienic stainless steel cooking interior.
 4 tray levels.

Safety
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning
 Cleaning program.
 Drying program.
 Descaling programme.
 Grease filter, dishwasher-safe.

Planning notes
 Door hinge not reversible.
 No other electrical appliances should be installed above the BSP Combi-steam oven.
 The door panel front of the appliance extends 13/16" from the cabinet front.
 The outer edge of the door handle extends 2 13/16" from the cabinet front.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the 110° door opening angle.
 To achieve the 21 5/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
 The power outlet needs to be planned outside of the niche.

Rating
 Energy efficiency class A.
 Total rating 2.1 KW.
 Total Amps: 10 A.
 208 / 220 - 240 V / 60 Hz.
 Connecting cable 59 1/16 without plug (hardwire required).

