

DA 2518

Insert ventilation hood
with energy-efficient LED lighting and backlit controls for easy use.



- Customized kitchen design – fully integrated in 43 1/2 (1102) in (mm) width
- Unique user convenience – Con@ctivity
- Powerful – 500.29 (850) ft³/min (m³/h) in Booster level
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean – Miele CleanCover

EAN: 4002516024699 / Material number: 10876740 / Old Material Number: 28251855USA

Design	
Insert ventilation hood	•
Construction type and design	
Color	Stainless steel
Operating modes	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
OdorFree charcoal filter (order separately)	DKF 15-P
User convenience	
Miele@home	•
Automatic function Con@ctivity	•
Electronic controls	•
Power levels (number excl. Intensive)	3
Run-on time 5/15 min.	•
Booster levels	1
Programmable Intensive switch-off	•
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
CleanCover	•
Filter system	
Number of dishwasher-safe stainless-steel grease filters	3
Lighting	
LED	•
Number x W	4 x 3 W
Light intensity in Lx	520 lx
Color temperature in K	3000 Kelvin
Blower	
Dual-action blower	•
AC motor	•
Exhaust air	
Maximum air throughput in cfm according to HVI	415
Air throughput	Values upon request
Air throughput in Intensive setting (cfm)	500.29 (850)
Air throughput in Booster level 1 (m ³ /min)	850.0
Safety	
Safety shut-off	•
Technical data	
Canopy width in in.(mm)	43 1/2 (1102)
Canopy height in in.(mm)	2 (50)
Canopy depth in in.(mm)	15 7/8 (402)
Minimum height above electric hobs in mm	24 1/8 (610)
Net weight in lbs. (kg)	32 (14.3)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Minimum height above gas cooktop (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1

DA 2518

Insert ventilation hood

with energy-efficient LED lighting and backlit controls for easy use.



EAN: 4002516024699 / Material number: 10876740 / Old Material Number: 28251855USA

Frequency in Hz	60
Installation note	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Communication module for Con@ctivity XKM 2000 DA	XKS 3000 Z
Non-return flap	•