

DA 6891

36-inch downdraft ventilation hood

optional external or internal blower for maximum versatility.



- Striking design – telescopic canopy 36 1/8 (916) in (mm) inches wide.
- Powerful – ?? in Booster level
- Practical – 15-minute automatic blower run-on
- Suitable for every home – vented or recirculating
- For perfect functionality – accessories for proper venting

EAN: 4002515823972 / Material number: 10595910 / Old Material Number: 28689150USA

Design	
Downdraft extractor system	•
Construction type and design	
Color	Stainless steel
Operating modes	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 2900-900
OdorFree charcoal filter (order separately)	DKF 18-900
Design	
Edge extraction	•
User convenience	
Electronic controls	•
Power levels (number excl. Intensive)	3
Booster levels	1
Run-on time 15 min.	•
Hood in Motion	•
Filter system	
Dishwasher-safe grease filters	2
Lighting	
Number x W	1x6W
Light intensity in Lx	280 lx
Color temperature in K	4000 Kelvin
Exhaust air	
Maximum air throughput in cfm according to HVI	240
Safety	
Safety shut-off	•
Single-ply safety glass (ESG)	•
Technical data	
Overall min. height for vented and external in in. (mm)	41 1/2 (1052)
Canopy width in in.(mm)	36 1/8 (916)
Overall max. height for vented and external in in. (mm)	41 1/2 (1052)
Canopy height in in.(mm)	25 1/2 (646)
Overall min. height for recirculation in in. (mm)	41 1/2 (1052)
Canopy depth in in.(mm)	13 7/8 (351)
Overall max. height for recirculation in in. (mm)	41 1/2 (1052)
Net weight in lbs. (kg)	60 (27.0)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Total connected load in kW	0.34
Voltage in V	120
Fuse rating in A	10
Number of phases	1
Frequency in Hz	60
Installation note	
Vent connection at top,rear,side,bottom	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Reducer from 150 to 125 mm Ø	•

