30-Inch Induction Range

TRANSITIONAL









Features & Benefits

- · Dual Four-Part Pure Convection system
- · Anti-scratch matte glass cooking surface
- · Bridge Element
- · Dual Noise Cancellation for quiet induction operation
- LCD control panel with SmartThings Wi-Fi connectivity
- · Auto Connect to compatible ventilation through Bluetooth
- · Air Sous Vide and Air Fry
- · Digital temperature probe
- · Self-clean oven
- · Softshut hinges
- · Voice commands through Bixby/Alexa/Google
- · Energy Star Certified

Controls	
CONTROL TYPE	2.25" Touchscreen + Knobs
ILLUMINA KNOBS	White
WI-FI + SMARTTHINGS	Yes
BLUETOOTH AUTO CONNECT™ VENTILATION	Yes
CLOCK	Yes
KITCHEN TIMER	Yes
CHILD LOCK	Yes
SABBATH MODE	Yes

OVEN CAPACITY (GU. FT.) CONVECTION BAKE ELEMENT 3,000W BROIL ELEMENT 4,200W CONVECTION ELEMENT 1,3000W TEMPERATURE PROBE LIGHTING SELF-CLEAN Self-Clean, GreenClean M Yes COOKTOP COOKING ZONES 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7" LEFT REAR (W) RIGHT FRONT (W) RIGHT FRONT (W) RIGHT REAR (W) RIGHT REAR (W) PRIDGE Yes (left front & left rear) Weights & Dimensions NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) PRODUCT DIMENSIONS (W × H × D IN INCHES) Technical Details ELECTRICAL REQUIREMENTS 2 Years		
CONVECTION Dual Four-Part Pure Convection BAKE ELEMENT 3,000W BROIL ELEMENT 4,200W CONVECTION ELEMENT 1,3000W TEMPERATURE PROBE Yes LIGHTING Halogen Self-Clean, GreenClean™ SOFTSHUT™ Yes Cooktop 4 COOKING ZONES 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7" RIGHT FRONT (W) 2,400 (4,300 boost) - 7" RIGHT FRONT (W) 1,200 (2,000 boost) - 6" BRIDGE Yes (left front & left rear) Weights & Dimensions NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) 29 ½ x 36 to 36 ¾ x 27 ½ Technical Details 29 ½ x 36 to 36 ¾ x 27 ½ ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	Oven	
BAKE ELEMENT ### 3,000W ### CONVECTION ELEMENT ### 1,3000W ### TEMPERATURE PROBE LIGHTING ### Halogen ### Self-Clean, GreenClean™ ### Yes ### Cooktop ### Cooktop ### Cooking Zones ### 4 ### LEFT FRONT (W) ### 1,800 (2,300 boost) - 7" ### LEFT REAR (W) ### 1,800 (2,300 boost) - 11" ### RIGHT FRONT (W) ### 1,200 (2,000 boost) - 6" ### BRIDGE ### Yes (left front & left rear) ### Weights & Dimensions ### NET WEIGHT (LBS.) ### 237.8 ### SHIPPING WEIGHT (LBS.) ### PRODUCT DIMENSIONS (W × H × D IN INCHES) ### 240v, 60 Hz, 40A ### Warranty ### Warranty	OVEN CAPACITY (CU. FT.)	6.3
## BROIL ELEMENT 4,200W CONVECTION ELEMENT 1,3000W TEMPERATURE PROBE Yes LIGHTING Halogen Self-Clean, GreenClean™ Yes Cooktop Cooking zones 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7™ LEFT REAR (W) 1,800 (2,300 boost) - 11™ RIGHT FRONT (W) 1,200 (2,000 boost) - 6™ BRIDGE Yes (left front & left rear) Weights & Dimensions NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) 29 15% x 36 to 36 3/4 x 27 3/6 Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	CONVECTION	Dual Four-Part Pure Convection
CONVECTION ELEMENT 1,3000W TEMPERATURE PROBE Yes LIGHTING Halogen Self-Clean, GreenClean™ Yes Cooktop COOKING ZONES 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7" LEFT REAR (W) RIGHT FRONT (W) 1,200 (2,300 boost) - 11" RIGHT FRONT (W) PRIGHT FRONT (W) RIGHT REAR (W) RIGHT REAR (W) PRODUCT DIMENSIONS NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) 29 1% x 36 to 36 ¾ x 27 ½ 6 Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A	BAKE ELEMENT	3,000W
TEMPERATURE PROBE Yes LIGHTING Halogen SELF-CLEAN Self-Clean, GreenClean™ SOFTSHUT™ Yes Cooktop 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7" LEFT REAR (W) 1,800 (2,300 boost) - 7" RIGHT FRONT (W) 2,400 (4,300 boost) - 11" RIGHT REAR (W) 1,200 (2,000 boost) - 6" BRIDGE Yes (left front & left rear) Weights & Dimensions 237.8 SHIPPING WEIGHT (LBS.) 265.9 PRODUCT DIMENSIONS (W x H x D IN INCHES) 29 ½% x 36 to 36 ¾ x 27 ½% Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	BROIL ELEMENT	4,200W
Halogen	CONVECTION ELEMENT	1,3000W
SELF-CLEAN Self-Clean, GreenClean™ SOFTSHUT™ Yes Cooktop 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7" LEFT REAR (W) 1,800 (2,300 boost) - 7" RIGHT FRONT (W) 2,400 (4,300 boost) - 11" RIGHT REAR (W) 1,200 (2,000 boost) - 6" BRIDGE Yes (left front & left rear) Weights & Dimensions 237.8 SHIPPING WEIGHT (LBS.) 265.9 PRODUCT DIMENSIONS (W x H x D IN INCHES) 29 ½ x 36 to 36 ½ x 27 ½ Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	TEMPERATURE PROBE	Yes
Cooktop COOKING ZONES 4 LEFT FRONT (W) 1,800 (2,300 boost) - 7" LEFT REAR (W) 1,800 (2,300 boost) - 7" RIGHT FRONT (W) 2,400 (4,300 boost) - 11" RIGHT REAR (W) 1,200 (2,000 boost) - 6" BRIDGE Yes (left front & left rear) Weights & Dimensions 237.8 SHIPPING WEIGHT (LBS.) 265.9 PRODUCT DIMENSIONS (W×H×DININCHES) 29 ½ x 36 to 36 ¼ x 27 ½ Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	LIGHTING	Halogen
COOKING ZONES LEFT FRONT (W) LEFT REAR (W) RIGHT FRONT (W) RIGHT FRONT (W) RIGHT REAR (W)	SELF-CLEAN	Self-Clean, GreenClean™
COOKING ZONES LEFT FRONT (W) LEFT REAR (W) RIGHT FRONT (W) RIGHT FRONT (W) RIGHT REAR (W)	SOFTSHUT™	Yes
LEFT FRONT (W) 1,800 (2,300 boost) - 7" LEFT REAR (W) 1,800 (2,300 boost) - 7" RIGHT FRONT (W) 2,400 (4,300 boost) - 11" RIGHT REAR (W) 1,200 (2,000 boost) - 6" Weights & Dimensions NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) 265.9 PRODUCT DIMENSIONS (W x H x D IN INCHES) Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	Cooktop	
1,800 (2,300 boost) - 7"	COOKING ZONES	4
### RIGHT FRONT (W) ### RIGHT REAR (W) ### 1,200 (2,000 boost) - 6" ### BRIDGE ### Yes (left front & left rear) Weights & Dimensions **NET WEIGHT (LBS.)** **SHIPPING WEIGHT (LBS.)** **PRODUCT DIMENSIONS** (W x H x D IN INCHES)** **Technical Details** **ELECTRICAL REQUIREMENTS** **2,400 (4,300 boost) - 11" 1,200 (2,000 boost) - 6" **Yes (left front & left rear) **237.8 **240.** **PRODUCT DIMENSIONS** (W x H x D IN INCHES)** **265.9 **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **266.9 **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHES)** **PRODUCT DIMENSIONS* (W x H x D IN INCHE	LEFT FRONT (W)	1,800 (2,300 boost) - 7"
### RIGHT REAR (W) 1,200 (2,000 boost) - 6" Weights & Dimensions NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) PRODUCT DIMENSIONS (W x H x D IN INCHES) Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	LEFT REAR (W)	1,800 (2,300 boost) - 7"
Weights & Dimensions NET WEIGHT (LBS.) SHIPPING WEIGHT (LBS.) PRODUCT DIMENSIONS (W x H x D IN INCHES) Technical Details ELECTRICAL REQUIREMENTS Yes (left front & left rear) 237.8 237.8 2915/6 x 36 to 36 ¾ x 27 ¼6 Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A	RIGHT FRONT (W)	2,400 (4,300 boost) - 11"
Weights & Dimensions NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) PRODUCT DIMENSIONS (W×H×D IN INCHES) 29 ½ x 36 to 36 ¾ x 27 ½ Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	RIGHT REAR (W)	1,200 (2,000 boost) - 6"
NET WEIGHT (LBS.) 237.8 SHIPPING WEIGHT (LBS.) 265.9 PRODUCT DIMENSIONS (W x H x D IN INCHES) 29 ½ x 36 to 36 ¼ x 27 ½ Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty Varranty	BRIDGE	Yes (left front & left rear)
SHIPPING WEIGHT (LBS.) PRODUCT DIMENSIONS (W x H x D IN INCHES) Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	Weights & Dimensions	
PRODUCT DIMENSIONS (W x H x D IN INCHES) 29 ½ x 36 to 36 ¾ x 27 ½ Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	NET WEIGHT (LBS.)	237.8
Technical Details ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	SHIPPING WEIGHT (LBS.)	265.9
ELECTRICAL REQUIREMENTS 240v, 60 Hz, 40A Warranty	PRODUCT DIMENSIONS (W x H x D IN INCHES)	29 ½ x 36 to 36 ¼ x 27 ½
Warranty	Technical Details	
,	ELECTRICAL REQUIREMENTS	240v, 60 Hz, 40A
2 V	Warranty	
FULL COVERAGE 2 Years	FULL COVERAGE	2 Years