DW2451



FEATURES

Three powerful spray arms, 43 spray jets, and a fine-mesh filter work together to remove food and grease and circulate clean water

Every glass, dish, and utensil comes out spotless and dry thanks to the hot rinse and fan assist

Whisper-quiet operation means you can keep the conversation flowing while running a load of dishes

Quality and aesthetics meet in a striking stainless-steel interior with a clean, fastenerless design

12 wash cycles and 6 add-on options can be mixed and matched, allowing you to personalize cleaning to your needs

Offers infinite interior variations to meet your dishwashing needs; heightadjustable middle rack and fold-down tines accommodate large pots and tall items

Loading and unloading is easy with interior LED lights that aid in visibility

Dishwasher disappears into the kitchen with hidden control panel and discreet status light

With our convenient Owner's App, you can remotely start or monitor a cycle, receive alerts when rinse aid is low—even set up auto-replenishment

Cove's leak protection system offers peace of mind in the rare event of a leak. A conductivity sensor in the base of the unit will automatically stop a cycle in progress if it detects a leak

ACCESSORIES

4" Stainless Kickplate - 24" Opening

4" Stainless Kickplate - 60cm Opening

Pro Handle Kit

Tubular Handle Kit

24" Stainless Steel Door Panel Kits

60cm Stainless Steel Door Panel Kits

Accessories are available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.



PRO

PRODUCT DETAILS

DISHWASHER

- 4 LED lights (2 sides; 2 top)
- · 43 spray jets across 3 spray arms
- · Four-stage, fine mesh filter
- Adjustable stemware rail
- · Adjustable cup shelf
- · Height-adjustable middle rack
- Easy-glide bottom rack
- Upper silverware rack
- · One large utensil basket
- · Fold-down tines on lower and middle racks





PRODUCT SPECIFICATIONS

DW2451
23 5/8"W x 34 1/2"H x 23 1/4"D
26 3/4"
41 dBA (Model and cycle/option dependent)
115 VAC, 60 Hz
15 amp dedicated circuit
3-prong grounding-type
6'
5' braided tubing with 3/8" female compression fitting
5' (1.5 m) corrugated tubing
30–140 psi

ELECTRICAL

PLUMBING






COVE OPENING WIDTH Cove dishwashers accommodate varying opening widths. A 23 5/8" (60 cm) width provides minimum reveals and is ideal for new construction. A 24" width is also common; however, reveals for a 24" opening will be larger than the reveals for a 23 5/8" opening unless the panel width is adjusted accordingly. 24" and 60 cm stainless steel panels are available and must be specified accordingly.


PANEL SPECIFICATIONS For complete panels specifications including width/height, weight requirements and thickness requirements visit <u>subzero-wolf.com/reveal</u>.

INTERIOR VIEW




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.


DIMENSIONS



*33 3/4" (857) MIN TO 34 3/4" (883) MAX



24" INSTALLATION



NOTE: 31/2" (89) finished returns will be visible and should be finished to match cabinetry.

