

# FFAR10MED2



56.75" x 23.63" x 23.5" (H x W x D)

10.1 cu.ft. upright auto defrost medical/scientific all-refrigerator with digital thermostat and NIST calibrated thermometer/alarm; includes front lock, hospital grade cord, and internal fan

### Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

Assembled in the USA from domestic and imported components

### Product Features:

|   |  |
|---|--|
| Reliable temperature stability            | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions  |
| Digital thermostat                        | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience   |
| High/low temperature alarm                | Audible alarm sounds if the interior temperature rises or falls out of set range   |
| NIST calibrated temperature display       | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button  |
| Buffered temperature probe                | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |
| Factory installed lock                    | Keyed lock conveniently located towards the top of the door for added security (2 keys included)   |
| Automatic defrost                         | Reduced maintenance with auto defrost system   |
| Internal fan                              | Fan-forced cooling ensures the unit is evenly cooled from top to bottom  |
| Hospital grade cord with 'green dot' plug | Secure three-pronged cord for added unit safety in high traffic areas  |

## FFAR10MED2 Specifications:

| Overview                   |                     |
|----------------------------|---------------------|
| Height of Cabinet          | 56.75" (144 cm)     |
| Width                      | 23.63" (60 cm)      |
| Depth                      | 23.5" (60 cm)       |
| Depth with Handle          | 24.75" (63 cm)      |
| Depth with door at 90°     | 45.5" (116 cm)      |
| Capacity                   | 10.1 cu.ft. (286 L) |
| Defrost Type               | Automatic           |
| Door                       | White               |
| Cabinet                    | White               |
| US Electrical Safety       | ETL                 |
| Canadian Electrical Safety | ETL-C               |
| Other Energy Info          | 120 Volts / 60 Hz.  |
| Amps                       | 1.5                 |
| Weight                     | 140.0 lbs. (64 kg)  |
| Parts & Labor Warranty     | 2 Years             |
| Compressor Warranty        | 5 Years             |
| UPC                        | 761101056579        |
| Refrigerator Features      |                     |
| Door Swing                 | RHD                 |
| Reversible                 | Factory Reversible  |
| Shelf Type                 | Wire                |
| Shelf Qty                  | 4                   |
| Adjustable Shelves         | Yes                 |
| Thermostat Type            | Digital             |
| Fan Type                   | Interior            |
| Refrigerant Type           | R134a               |
| Refrigerant Amount         | 3.0oz.              |
| High Side PSI              | 285.0               |
| Low Side PSI               | 70.0                |
| Level Legs Qty             | 2                   |
| Interior Light             | Yes                 |
| Temperature Range          | 2°C to 8°C          |
| Dimensions                 |                     |
| Interior Height            | 48.25" (123 cm)     |
| Interior Width             | 20.5" (52 cm)       |
| Interior Depth             | 17.75" (45 cm)      |
| Compressor Step Height     | 6.25" (16 cm)       |

|                       |               |
|-----------------------|---------------|
| Compressor Step Width | 20.0" (51 cm) |
| Compressor Step Depth | 5.5" (14 cm)  |

