

FHDD5034Y1



Product Specifications

Dehumidifier		
Air CFM (Low)	174 CFM	
Air CFM (High)	235 CFM	
Fan Speeds - Fan	3	
Noise Level dBA (Low)	47 dBA	
Noise Level dBA (High)	51 dBA	
Motor RPM (Low)	890 RPM	
Motor RPM (High)	1160 RPM	
Air Discharge	Top of Unit	
Container Full Indication	Yes	
Digital Humidity Readout	Yes	
Dust Air Filter	Yes	
Filter Access Location	Rear	
Filter Check Indicator	Yes	
Low Temperature Operation	Yes	
Option for Advanced Filtration	No	
Pump Feature	No	

Functions

24-Hour On/Off Timer	Yes	
Auto Restart	Yes	
Auto Shut-Off	Yes	
Continuous Drain Operation	Yes	

Installation

Power Cord Length	72"
-------------------	-----

Dimensions and Volume

Height	24.7/10"
Width	16"
Depth	12 1/5"

Performance Certifications and Approvals		
Energy Efficiency Verification (Canada)	Yes	
ENERGY STAR Certified	Yes	

Performance

Bucket Capacity	2.7 Gallons	
Dehumidification - Pints per Day	50	
Relative Humidity Minimum	35 %	
Relative Humidity Maximum	85 %	
Integrated Energy Factor (L/kWh)	1.8	

Controls

Control Type	Electronic
--------------	------------

Electrical Specifications

Amps	8.5 Amps
Voltage Rating	115 V
Watts	430 Watts

General Specifications

Prop 65 Label	Yes
Refrigerant Type	R-32
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Connectivity

Wi-Fi Enabled	Yes
---------------	-----

Safety Certifications and Approvals

cUL Listed	Yes
UL Listed	Yes