



## 60 Pint Built-In Pump Dehumidifier

Dehumidifier

Available Products: FHDP6033W1

Available Colors: White

Version: 02/25

## Product Specifications

### Dehumidifier

|                                |             |
|--------------------------------|-------------|
| Air CFM (Low)                  | 247 CFM     |
| Air CFM (High)                 | 297 CFM     |
| Fan Speeds - Fan               | 2           |
| Noise Level dBA (Low)          | 53 dBA      |
| Noise Level dBA (High)         | 57 dBA      |
| Motor RPM (Low)                | 960 RPM     |
| Motor RPM (High)               | 1070 RPM    |
| Air Discharge                  | Top of Unit |
| Container Full Indication      | Yes         |
| Digital Humidity Readout       | Yes         |
| Dust Air Filter                | Yes         |
| Filter Access Location         | Rear        |
| Filter Check Indicator         | Yes         |
| Low Temperature Operation      | Yes         |
| Option for Advanced Filtration | No          |
| Pump Feature                   | Yes         |

### Functions

|                            |     |
|----------------------------|-----|
| 24-Hour On/Off Timer       | No  |
| Auto Restart               | Yes |
| Auto Shut-Off              | Yes |
| Continuous Drain Operation | Yes |

### Dimensions and Volume

|        |         |
|--------|---------|
| Height | 24 3/5" |
| Width  | 18 4/5" |
| Depth  | 14 1/5" |

### Installation

|                   |     |
|-------------------|-----|
| Power Cord Length | 72" |
|-------------------|-----|

### Performance Certifications and Approvals

|                                         |     |
|-----------------------------------------|-----|
| Energy Efficiency Verification (Canada) | Yes |
| ENERGY STAR Certified                   | No  |

### Accessories Sold Separately

|                |    |
|----------------|----|
| PureAir Filter | No |
|----------------|----|

### Performance

|                                  |             |
|----------------------------------|-------------|
| Bucket Capacity                  | 3.2 Gallons |
| Dehumidification - Pints per Day | 60          |
| Relative Humidity Minimum        | 35 %        |
| Relative Humidity Maximum        | 85 %        |
| Integrated Energy Factor (L/kWh) | 2.8         |

### Controls

|              |            |
|--------------|------------|
| Control Type | Electronic |
|--------------|------------|

### Electrical Specifications

|                |           |
|----------------|-----------|
| Amps           | 3.8 Amps  |
| Voltage Rating | 115 V     |
| Watts          | 425 Watts |

### General Specifications

|                  |        |
|------------------|--------|
| Prop 65 Label    | Yes    |
| Refrigerant Type | R-32   |
| Warranty - Labor | 1 Year |
| Warranty - Parts | 1 Year |

### Connectivity

|               |    |
|---------------|----|
| Wi-Fi Enabled | No |
|---------------|----|

### Safety Certifications and Approvals

|            |     |
|------------|-----|
| cUL Listed | Yes |
| UL Listed  | Yes |