

## G 7216 SCU

### 24" Pre-Finished Dishwasher

#### Features:

- DirectSelect Controls
- QuickIntenseWash - a full wash and dry cycle in 58 minutes
- 42 dBA
- 3D MultiFlex Cutlery Tray
- CleanTouch Steel - easy to clean, fingerprint resistant stainless steel
- Water Softener
- EnergyStar



#### MATERIAL #

12497130

| SPECIFICATIONS                       |   |
|--------------------------------------|---|
| Overall Unit Dimensions              | 23 <sup>9</sup> / <sub>16</sub> " (598 mm) W x 33 <sup>11</sup> / <sub>16</sub> " - 36 <sup>1</sup> / <sub>4</sub> " (855 - 920 mm) H x 22 <sup>7</sup> / <sub>16</sub> " (570 mm) D<br>[Depth does not include door panel] |
| Niche                                |   |
| Minimum Cabinet Niche Opening        | 23 <sup>5</sup> / <sub>8</sub> " (600 mm) W x 33 <sup>3</sup> / <sub>4</sub> " (857 mm) H x 22 <sup>7</sup> / <sub>16</sub> " (570 mm) D  |
| Plumbing                             |   |
| Water Supply Requirements            | <ul style="list-style-type: none"> <li>• Cold or Hot (max 150°F/65°C) water connection</li> <li>• Male 3/8" compression fitting</li> <li>• Water pressure range 7.25 psi (0.5 bar) and 145 psi (10 bar)</li> </ul>          |
| Water Connection Line (Supplied)     | Length: 5 ft (1.5 m)<br>Female 3/8" compression.  |
| Drain Hose (Supplied)                | Length: 5 ft (1.5 m)<br>7/8" (22 mm) internal diameter  |
| Electrical                           |   |
| Electrical Requirements              | 110V / 120V, 60Hz, 15 Amps  |
| Power Cord (Convertible to hardwire) | NEMA 5-15 plug, 5 ft (1.52 m)   |
| Shipping                             |   |
| Shipping Weight                      | 121 lbs (55 kg)   |
| Shipping Dimensions                  | 27 <sup>1</sup> / <sub>8</sub> " W x 38 <sup>1</sup> / <sub>8</sub> " H x 26 <sup>3</sup> / <sub>8</sub> " D  |

#### PRODUCT AND CUTOUT DIMENSIONS

