# MOLF

#### GR304



#### **FEATURES**

Control temperature precisely with four dual-stacked, sealed gas burners for higher highs, lower lows

Enjoy quicker heat and more even cooking with this large capacity gas convection oven

Produce crisper crusts and faster sears with the powerful infrared interior broiler

Re-ignites flame automatically with our spark ignition system for improved temperature control and added safety

Move pots and pans easily across continuous cast-iron grates

Clean up sloshes and spills easily with the seamless, sealed, black porcelain-coated burner pans

Find your kitchen style with a choice of iconic red, black, or brushed stainless control knobs

#### ACCESSORIES

#### 2-Burner Wok Grate

2-Burner Wok Grate

Bake Stone Kit

Filler Trim

Front Leg Covers

Full-Extension Ball Bearing Rack

Stainless Steel Kickplate

Stainless steel, brass or chrome bezels

High altitude conversion kits available

Signature red, black or stainless steel control knobs

5" and 10" stainless steel risers, and 20" riser with shelf

Accessories available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.




#### **KNOB OPTIONS**





#### **TOP CONFIGURATION**



### **RANGETOP SPECIFICATIONS**

- 1 9,200 Btu burner
- 3 15,000 Btu burners

### **OVEN INTERIOR SPECIFICATIONS**


- 30,000 Btu oven burner
- 18,000 Btu oven broiler

### **PRODUCT SPECIFICATIONS**

Model	GR304
Dimensions	29 7/8"W x 37"H x 28 3/8"D
Oven 1 Interior Dimensions	24"W x 18 5/8"H x 17"D
Oven 1 Usable Capacity	2.5 cu. ft.
Oven 1 Overall Capacity	4.4 cu. ft.
Door Clearance	19 1/2"
Weight	413 lbs
Electrical Supply	110/120 VAC, 50/60 Hz
Electrical Service	15 amp dedicated circuit
Gas Supply	3/4" ID line
Gas Inlet	1/2" NPT female
Receptacle	3-prong grounding-type


#### ELECTRICAL

GAS




NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

#### DIMENSIONS



### STANDARD INSTALLATION



\*Without ventilation hood, 42" (1067) minimum clearance countertop to combustible materials, charbroiler and GR488 require non-combustible materials.

NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces, combustible materials cannot be located within this area.

For island installation, 12" (305) minimum clearance back of range to combustible rear wall above countertop.

## MOLF