



24" C-SERIES
Wine Reserve



ecofriendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION
HC24WB-4-1R/L	Indoor C-Series Wine Reserve Solid Stainless Steel Door
HC24WB-4-2R/L	Indoor C-Series Wine Reserve Solid Panel Ready Door
HC24WB-4-3R/L	Indoor C-Series Wine Reserve Stainless Steel Glass Door
HC24WB-4-4R/L	Indoor C-Series Wine Reserve Panel Ready Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- Superior construction provides ideal combination of energy efficient operation & powerful refrigeration performance ideal for food and beverages
- 800 BTU/hr capacity delivers commercial grade cooling performance
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications
- Wine shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time

Quick Features:

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 45 bottles of wine



24" C-SERIES
Wine Reserve

MODEL NUMBERS		HC24WB
MODEL DESCRIPTION		24" Indoor Wine Reserve
ATTRIBUTES		
Perlick Anti-Condensation System		NO
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		5.2 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		195 lbs (88.45 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.9 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (62g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	45° (7.2°) - 65° (18.3°) Factory Set Point 55° (12.7°)
	Heat Rejection (at 75°F)	450 BTU/hr
	Pull Down Capacity	800 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736	Caster Kit for HP24/HC24/HA24 models
67115-24	Wood Faces for Wine Shelf (7/pk)

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about **Prop 65**, go to P65Warnings.ca.gov.



24" C-SERIES
Wine Reserve

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HC24WB-4-1L	HC24WB4F-00-SLS0W	Left	No
HC24WB-4-1R	HC24WB4F-00-SRS0W	Right	No
HC24WB-4-2L	HC24WB4F-00-PL00W	Left	No
HC24WB-4-2R	HC24WB4F-00-PR00W	Right	No
HC24WB-4-3L	HC24WB4F-00-TLS0W	Left	No
HC24WB-4-3R	HC24WB4F-00-TRS0W	Right	No
HC24WB-4-4L	HC24WB4F-00-RL00W	Left	No
HC24WB-4-4R	HC24WB4F-00-RR00W	Right	No
HC24WB-4-1LL	HC24WB4F-00-SLSLW	Left	Yes
HC24WB-4-1RL	HC24WB4F-00-SRSLW	Right	Yes
HC24WB-4-2LL	HC24WB4F-00-PL0LW	Left	Yes
HC24WB-4-2RL	HC24WB4F-00-PR0LW	Right	Yes
HC24WB-4-3LL	HC24WB4F-00-TLSLW	Left	Yes
HC24WB-4-3RL	HC24WB4F-00-TRSLW	Right	Yes
HC24WB-4-4LL	HC24WB4F-00-RL0LW	Left	Yes
HC24WB-4-4RL	HC24WB4F-00-RR0LW	Right	Yes



24" C-SERIES
Wine Reserve

