800 Series Downdraft - HDD80052UC





HDD80052UC Stainless Steel

Sleek, built-in, and retracts out of sight. Bosch 30" Downdraft's flexible design seamlessly integrates into your kitchen

Features & Benefits

Beautifully designed to preserve clean sight lines when not in use

Sleek front panel filter design acts as a guard against splatters

6 exhaust connections possible (transition sold separately)

Recirculation kit for sale for use in non ducted applications*

General Properties					
Operating mode	Convertible: ducted / recirculating				
Maximum CFM	Blower sold separately				
Number of speed settings	3-stage				
Motor location	External				
Damper included	No				
Grease filter material	Aluminum				
Grease filter type	Multilayer cassette				
Duct direction	Front, Left, Right, Rear, Down				
Optional blower required	Yes (600 CFM options sold separately)				
Technical Details					
Volts	120 V				
Frequency	60 Hz				
Plug type	120V-3 prong				
Power cord length	30"				
Dimensions & Weight					
Overall appliance dimensions (width of canopy included) (HxWxD)	44 ³ /8" x 31" x 2 ³ /4"				
Height of the rise	15"				
Diameter of air duct- internal	8"				
Diameter of air duct- external	6" or 8"				
Net weight	37 lbs				
Accessories - Required					
DI / II					

Accessories - Transitions	& Blowers			
6" side / rear / downward transition	HDDSTRAN6			
8" side / rear / downward transition	HDDSTRAN8			

NOTE: HDDSTRAN6 or HDDSTRAN8 required for side, rear or downward exhaust applications with inline and remote blowers.

6" round front plate	HDDFTRAN6
8" round front plate	HDDFTRAN8

NOTE: HDDFTRAN6 or HDDFTRAN8 required for front exhaust applications with inline and remote blowers.

Transition for rectangular duct	HDDSTRAN2
2' rectangular duct	HDD2RECTD

NOTE: HDDSTRAN2 needed to attach HDD2RECTD to downdraft. For use with installation of inline or remote blower applications.

600 CFM flexible blower	DHG602DUC
600 CFM inline blower	DHI1FZUC
600 CFM remote blower	DHR1FZUC
Accessories - Optional	
Recirculation kit (compatible with electric and induction cooktops only)	HDDREC5UC
01 1 611	

electric and induction cooktops only)	
Charcoal filter replacement for recirculation kit	HDDFILTUC
30" gas cooktop seal kit for downdraft (required for installation with gas cooktops)	HDD0RSP
Trim kit for 30" FlameSelect® gas cooktops	HDDTRIM30S



Blower (sold separately)

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

^{*}Recirculation kit is not compatible with gas cooktop installations with downdraft


800 Series Downdraft - HDD80052UC



HVI Performance Values (CFM & Sones)

Downdraft HDD80052UC with Blower DHG602DUC										
			Pressure (in. H2O)		Power (W)		CFM		Sones	
Exhaust	Duct Size	Required Accessories	High Speed	Working Speed	High Speed	Working Speed	High Speed	Working Speed	High Speed	Working Speed
Front	8" Round	None	0.1	0.018	285	68.5	380	160	12.0	2.0
Left	8" Round	Optional Adapter Model: HDDSTRAN8	0.1	0.016	279	67.0	360	150	11.0	2.5
Right	8" Round		0.1	0.017	288	65.7	350	140	11.0	1.4
Rear	8" Round		0.1	0.018	279	66.9	360	150	10.0	1.5
Bottom	8" Round		0.1	0.018	286	66.0	370	150	11.0	1.5
Front	8" Round	None	0.25	_	_	_	360	_	_	_
Left	8" Round	Optional Adapter Model: HDDSTRAN8	0.25	_	_	_	340	_	_	_
Right	8" Round		0.25	_	_	_	330	_	_	_
Rear	8" Round		0.25	_	_	_	340	_	_	_
Bottom	8" Round		0.25	_	_	_	350	_	_	_

Installation Details




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

800 Series Downdraft - HDD80052UC



Installation Details - Cutouts




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

800 Series Downdraft - HDD80052UC



Accessories - Optional







Trim Kit for 30" FlameSelect® Gas

Cooktops

30" trim kit for installation with 30" FlameSelect® gas cooktops

- ▶ Includes trim kit and installation tool
- Required for installation with 30" FlameSelect[®] gas cooktops






Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST).

Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

800 Series Downdraft - HDD80052UC



Flexible Blower Installation - Rear Exhaust Example




Required Accessories

HDDSTRAN8

8" Side / Rear / Downward Transition for Downdraft 8" Round transition enable ducting to be at sides, rear or below downdraft for flexible configurations to maximize your kitchen design


NOTE: HDDSTRAN8 side / rear / downward transition required for side, rear or downward exhaust applications with inline and remote blowers.



Application

- Rear exhaust option is possible if ducting is more convenient with this configuration
- Requires at least 18" of clearance to fit the blower and transition
- Blower must be accessible for maintenance
- Can be used with optional Recirculation Kit, sold separately
- Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC


600 CFM Flexible Integral

600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors



HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops




NOTE: Some applications may require deeper cabinets. Side and rear exhaust require at least 18" of clearance to fit the blower and / or ductwork. Refer to installation instructions.

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

800 Series Downdraft - HDD80052UC



Flexible Blower Installation - Downward Exhaust Example




Required Accessories

HDDSTRAN8

8" Side / Rear / Downward Transition for Downdraft 8" Round transition enable ducting to be at sides, rear or below downdraft for flexible configurations to maximize your kitchen design


NOTE: HDDSTRAN8 side / rear / downward transition required for side, rear or downward exhaust applications with inline and remote blowers.



Application

- Downward exhaust option if ducting is more convenient with this configuration
- Requires at least 18" of clearance to fit the blower and transition
- · Can be used with optional Recirculation Kit, sold separately
- Elbow, ductwork, blower support structure frame not included
- · Blower must be accessible for maintenance
- Can also be installed with inline and remote blowers

Required Blower



DHG602DUC

600 CFM Flexible Integral


600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

measurements in inches and (mm)

Optional Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking



HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors



HDD0RSP

30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops




Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

800 Series Downdraft - HDD80052UC




Flexible Blower Installation - Recirculation Example





Required Accessories

HDDREC5UC

Recirculation Kit for Downdraft When ducting to the exterior is not feasible, downdraft recirculation kit allows filtered air to reenter the kitchen while cooking








Application

- Allows for non-ducted downdraft installation by eliminating the need to exhaust to the exterior of the home
- Mount to toe kick or base of a cabinet and attach directly to flexible
- Recirculation module and metal grill vent plate placement can be rotated for flexible exhaust placement
- Elbow, ductwork, blower support structure frame not included

Required Blower



DHG602DUC

600 CFM Flexible Integral

600 CFM flexible blower can mount to downdraft or be used as an inline blower, and can be rotated to exhaust downward or to sides

Optional Accessories

HDDFILTUC

Charcoal Filter Replacement for Recirculation Kit for Downdraft

Maintain performance of Bosch downdraft recirculation kit with timely replacement of charcoal filter to capture and filter odors



30" Gas Cooktop Seal Kit for Downdraft 30" gas cooktop seal kit required for installation with 30" gas cooktops



Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.