

K 31222 Ui Built-under refrigerator Compact design with a practical interior layout.




- Optimum and maintenance-free LED lighting in compartment
- Door shelves can be cleaned in the dishwasher ComfortClean


EAN: 4002515952566 / Material number: 10799700 / Old Material Number: 36312220USA


Amulianas askaman	
Appliance category	
Fridge	•
Design	
Built-in	
Built-in integrated	
Built-in built-under	
Door hinge side	right
Convertible hinging	•
Design	
Type of lighting	LED
User convenience	
ComfortClean	•
Control	
Electronic temperature display and control	PicTronic
Independent temperature control of fridge and freezer compartments	No
Super Cooling	•
No. of temperature zones	1
Fridge/fridge zone	
No. of shelves	4
Number of door racks for cans	1
Door rack for bottles	1
Safety	
	•
LOCK TUNCTION	•
Lock function Acoustic door alarm	•
Acoustic door alarm	•
Acoustic door alarm Technical data	23 5/8 (600)
Acoustic door alarm Technical data Niche width in inches (mm), min.	23 5/8 (600) 23 5/8 (600)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max.	23 5/8 (600)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min.	23 5/8 (600) 32 3/8 (820)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max.	23 5/8 (600) 32 3/8 (820) 34 3/4 (880)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA) Voltage in V Fuse rating in A	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA) Voltage in V Fuse rating in A Number of phases	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115 10
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA) Voltage in V Fuse rating in A Number of phases Frequency in Hz	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115 10 1
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA) Voltage in V Fuse rating in A Number of phases Frequency in Hz Wire length in ft (m)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115 10 1 60 6 (1.9)
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA) Voltage in V Fuse rating in A Number of phases Frequency in Hz Wire length in ft (m) Replacing bulbs	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115 10 1
Acoustic door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Weight in lbs.(kg) Type of mounting Maximum fridge compartment door front weight in lbs. (kg) Total usable capacity in cu. ft. (l) Current consumption in milliampere (mA) Voltage in V Fuse rating in A Number of phases Frequency in Hz Wire length in ft (m)	23 5/8 (600) 32 3/8 (820) 34 3/4 (880) 21 3/4 (550) 23 5/8 (597) 32 3/8 (820) 21 3/4 (550) 79 (35.7) Fixed door 23 (10) 4.8 (136) 2300 115 10 1 60 6 (1.9)



K 31222 Ui Built-under refrigerator Compact design with a practical interior layout.







[mm]

K31222Ui, K31222Ui-1, K31225Ui, K31252Ui, K31252Ui-1, K31242UiF, K31242UiF-1, F31202Ui (installation drawings)

K31222Ui, K31222Ui-1, K31225Ui, K31252Ui, K31252Ui-1, K31242UiF, K31242UiF-1, F31202Ui, side view (installation draw)

K31222Ui, K31222Ui-1, K31225Ui, K31252Ui, K31252Ui-1, K31242UiF, K31242UiF-1 F31202Ui (installation drawings)