

KM 6375 Induction Cooktop with PowerFlex cooking area for maximum versatility and performance.



- Quick selection using numerical linear keybanks – Direct control plus
- Modern design 35 7/8 (911) in (mm) wide for flush-mounted installation
- Versatile and fast 5 cooking zones incl. 1 PowerFlex area
- Communication with the ventilation hood automatic Con@ctivity function
- Broad performance spectrum keep warm function and TwinBoost

EAN: 4002515472781 / Material number: 09775920 / Old Material Number: 26637562USA

Heating type	
Fuel type	Induction
Design	
Independent of oven	•
Design	
Elegant glass ceramic surface	•
Flush	•
Ceramic surface colour	Black
Print design	LightPrint
Cooking zone details	
No. of rings	5
PowerFlex cooking zones	
No.	2
Diameter in inches	Ø 150 – 230
Power in W	2200
Booster in W	3100
TwinBooster in W	3850
1st cooking zone/cooking area	
Position	Left
Type	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	5000
Max. rating in W	3550
Max. TwinBooster power rating in W	7700
2nd cooking zone/cooking area	useu seetsu
Position	rear center
Type	Variable cooking zone
Size in mm	Ø 140-200
Max. Booster power rating in W	2600
3rd cooking zone/cooking area	
Position	rear right
Type	Variable cooking zone
Size in mm	Ø 180-280
Max. Booster power rating in W	3100
Max. rating in W	2500
4th cooking zone/cooking area	
Position	front center
Туре	Variable cooking zone
Size in mm	Ø 100-160
Max. Booster power rating in W	1900
Max. rating in W	1450
User convenience	
Operation via sensor controls	Multiple direct dial
Automatic function	Con@ctivity 2.0
Pan and pan size recognition	•
Display colour	Red
Auto heat-up	•
Keeping warm	•
Stop & Go function	•
Safety switch-off	•



KM 6375 Induction Cooktop with PowerFlex cooking area for maximum versatility and performance.




EAN: 4002515472781 / Material number: 09775920 / Old Material Number: 26637562USA

Minute minder	•
Cleaning convenience	
Easy to clean ceramic glass	•
Safety	
Safety cut-out	•
Lock function	•
System lock	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions (width) in in. (mm)	35 7/8 (911)
Dimensions (height) in in. (mm)	4 7/8 (121)
Dimensions in mm (depth)	20 1/4 (512)
Casing height incl. connection box in mm	5 1/8 (128)
Internal cutout dimensions in mm (width) with flush installation	889
Internal cutout dimensions in mm (depth) with flush installation	490
Weight in lbs. (kg)	59 (27)
External cutout dimensions in mm (width) with flush installation	915
External cutout dimensions in mm (depth) with flush installation	516
Total connected load in kW	11.50
Power cord length in in. (m)	3 (1.2)
Voltage in V	240
Frequency in Hz	60
Standard accessories	
Power cord	Yes


Míele

KM 6375 Induction Cooktop

with PowerFlex cooking area for maximum versatility and performance.



20 5/16" (516+1mm) (612+1mm) (19 5/16" (12 mm) (10 mm)



KM 6375 (Installation drawing)


1) Front, 2) Casing depth, 3) Flexible metal Extension hose L = 47 1/4" (1200 mm), 4) Stepped cut-out, 5) Data plate

KM 6375 (Installation drawing)

4) Wooden frame 1/2" / 13 mm (not supplied with appliance)

KM 6375 (Installation drawing)

1) Worktop, 2) Hob, 3) Width of gap



KM 6375 (Installation drawing)