

## KM 7740 FR Induction Cooktop with 5 round cooking zones



- Intuitive quick selection via number sequences Smart Select
- Versatile 5 cooking zones, 1 extra large with diameter of 11 in
- With a width of 36 1/8 (915) in (mm) and stainless steel frame for proudmounting
- Shortest heating-up times TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611509 / Material number: 12074220 / Old Material Number: 26774000USA

0 ).	
Fuel type	Induction
Design	
Independent of oven	•
Design	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless steel frame	•
Proud installation	•
Cooking zone details	
No. of rings	5
Number of cooking areas	0
Maximum number of pans	5
1st cooking zone/cooking area	
Position	front left
Туре	Variable cooking zone
Size in mm	Ø 100-160
Max. Booster power rating in W	1700
Max. rating in W	1400
Max. TwinBooster power rating in W	2200
2nd cooking zone/cooking area	
Position	rear left
Type	Variable cooking zone
Size in mm	Ø 160-230
Max. Booster power rating in W	3000
Max. rating in W	2300
Max. TwinBooster power rating in W	3700
3rd cooking zone/cooking area	0.00
Position	Centered
Туре	Variable cooking zone
Size in mm	Ø 180-280
Max. Booster power rating in W	3000
Max. rating in W	2600
Max. TwinBooster power rating in W	3700
4th cooking zone/cooking area	0,00
Position	rear right
Туре	Variable cooking zone
Size in mm	Ø 140-190
Max. Booster power rating in W	2500
Max. rating in W	1850
Max. TwinBooster power rating in W	3000
5th cooking zone/cooking area	3000
Position	front right
Type Size in mm	Variable cooking zone Ø 140-190
Size in mm Max. rating in W	<del></del>
	1850
Max. booster rating in W	2500
Max. TwinBooster rating in W	3000
User convenience	



## KM 7740 FR Induction Cooktop with 5 round cooking zones



EAN: 4002516611509 / Material number: 12074220 / Old Material Number: 26774000USA

Operation via sensor controls	Smart Select
Pan and pan size recognition	•
Display colour	Yellow
Auto heat-up	•
Permanent pan recognition	•
Keeping warm	•
Stop & Go function	•
Recall function	•
Safety switch-off	•
Individual setting options (e.g. buzzers)	•
Wipe protection	•
Minute minder	•
Cleaning convenience	
Easy to clean ceramic glass	•
Safety	
Safety cut-out	•
Lock function	•
System lock	•
Integrated cooling blower	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions (width) in in. (mm)	36 1/8 (915)
Dimensions (height) in in. (mm)	3 1/8 (78)
Dimensions in mm (depth)	21 1/2 (544)
Cutout dimensions (width) in in. (mm)	34 1/2 (876)
Cutout dimensions (depth) in in. (mm)	20 1/2 (518)
Casing height incl. connection box in mm	2 7/8 (71)
Weight in lbs. (kg)	46 (21)
Total connected load in kW	9.90-11.50
Power cord length in in. (m)	3 (1.2)
Voltage in V	0
Frequency in Hz	60
Standard accessories	
Power cord	Yes