



P205UC | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower P205UC brings you power, protection, and versatility — all in one compact unit. Featuring 2 AC power outlets with 500J of surge protection, 2 USB-A charging ports and 1 USB-C charging port (USB-C not intended for use with laptops). It's perfect for desk tops, table tops or other high-traffic areas of the home or office.

TYPICAL APPLICATIONS

- Personal Electronics
- Wireless Speakers
- Cell Phones
- Tablets

FEATURES

- AC Outlets: 2
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 500 Joules
- USB-A Ports: 2
- USB-A Output: 2.4A (shared)
- USB-C Ports: 1
- USB-C Output: 15W
- Cord Length: 5 ft
- Plug Type: NEMA 5-15P
- Plug Style: Right Angle 45°
- Electrical Rating: 125V/13A/60Hz
- Connected Equipment Guarantee: \$25,000
- Warranty: One-Year Warranty



SPECIFICATIONS

INPUT	
Cord Length	5 ft (1.5 m)
Input Voltage	125 VAC
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	2 - NEMA 5-15R
Outlets - Total	2
Output Voltage	125 VAC
Output Watts - Continuous	1,875 W

OUTPUT - CONT.	
USB Charge Port	Yes
USB Charge Port Amperage	2.4 A (Shared)
USB Charge Port Quantity	3
USB Charge Port Type	2 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	15 Watts

P205UC

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Clamping Voltage	800V (H-N)
Maximum Surge Current	15,000 A
Maximum Surge Current H-N	15,000 A
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J

PHYSICAL

Color	White
Keyhole Mounting Slots	No

PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	11.0 x 3.51 x 11.0 cm
Physical Dimensions - WxHxD (mm)	110 x 35 x 110 mm
Physical Dimensions - WxHxD (in.)	4.33 x 1.38 x 4.33 in.
Weight (kg)	0.37 kg
Weight (lb)	0.81 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	11.99 x 15.01 x 8.0 cm
Shipping Dimensions - WxHxD (mm)	119.89 x 150.11 x 80.01 mm
Shipping Dimensions - WxHxD (in)	4.72 x 5.91 x 3.15 in.
Weight (kg)	0.41 kg
Weight (lb)	0.91 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1449 4th Edition, UL 1310, FCC Part 15B, DOE VI

WARRANTY

CEG Amount	\$25,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited Warranty