30" LOW PROFILE WALL HOOD

NOLF

PW302210

FEATURES

Breathe cleaner air and enjoy less greasy residue in your kitchen

Make a statement with a stainless professional look or opt for lowerprofile "hidden" ventilation

Matches the same heavy-duty stainless-steel construction, handfinished hemmed edges, and welded seams of all Sub-Zero, Wolf, and Cove products

Select from internal, in-line, or remote blower options (blower required)

Illuminates your cooking area with LED lighting with two brightness settings

Rely on a heat sentry that automatically turns on the blower or increases its speed when exhaust temperatures exceed 200 degrees Fahrenheit

Minimizes the backward flow of cold air with backdraft transition

ACCESSORIES

3 1/4" x 14" to 10" Round Transition

30" Recirculating Kit

Backsplash

Backsplash with Warming Racks

Make-Up Air Damper

Recirculating Filter

Inline Blowers

Internal Blowers

Remote Blowers

30" Pro Wall Hood Duct Covers

Accessories available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.




BLOWER OPTIONS

- 500 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS


Model	PW302210
Dimensions	30"W x 10"H x 22"D
Weight	39 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical or Horizontal
Discharge Dimensions	Rectangle 14" x 3 1/4"
Bottom of Hood to Countertop	30" to 36"


ELECTRICAL



 $\ensuremath{\operatorname{\textbf{NOTE:}}}$ Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS





MOLF