



**RC462705**  
**400 series refrigeration column**  
**With fresh cooling 32 °F**  
**Fully integrated, panel ready**  
**Niche width 24" (61 cm)**



Stainless steel interior with solid anthracite aluminium elements  
 Warm white and glare-free LED light spots  
 Opening assist for door with two options:  
 1. Push-to-open function for integration into handleless furniture front  
 2. Pull-to-open function to facilitate opening the door using a handle  
 The drawers in the RC and RF models are positioned at the same height.  
 With side-by-side installation, the glass shelves and door racks can be aligned on the same level  
 Flat stainless steel inner door, full-length  
 Almost invisible rail system for shelves and door racks for flexible positioning  
 Solid anthracite aluminium door racks  
 1 fresh cooling drawer 32 °F with temperature control from 32° F to 37 °F and one fresh cooling drawer with manually adjustable humidity  
 TFT touch display  
 Net volume 13 ft3 cu.ft. (367) litres  
 Energy Star certified

**Operation**  
 TFT touch display operation.  
 Clear text display in 44 languages.

**Technical Features**  
 Dynamic cold air distribution with Multi-Flow Air System.  
 Automatic defrosting with defrost water evaporation.  
 Cushioned door closing system.  
 Activated charcoal air filter.  
 Sabbath mode certified by Star-K.  
 When rest mode is active, the appliance can only be opened using a handle.  
 Open-door and malfunction warning system.  
 Home network integration for digital services (Home Connect) wireless via WiFi.  
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

**Cooling compartment**  
 Temperature adjustable from 35 °F to 46 °F.  
 1 shallow, fully extendable drawer with transparent front.  
 Cushioned closing system.  
 4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.  
 Flat door rail system with fully flexible positioning of door racks.  
 4 height-adjustable door racks, 1 of which is extra deep.  
 Net volume 314 l liters.

**Fresh cooling 32 °F**  
 1 large, fully extendable fresh cooling 32 °F drawer with transparent front, illuminated.  
 Cushioned closing system.  
 Temperature control via central TFT display, temperature can be adjusted from 30 °F to 38 °F.  
 Ideal for meat, fish and poultry.  
 Net volume 53 litres.

**Temperature controlled drawer**

**Product Features**  
**UPC code**  
 825225961062  
**Color / Material housing**  
**Variant color**  
 Not applicable  
**Panel ready**  
 Not possible  
**Silence level (dBA)**  
 40  
**Watts (W)**  
 350  
**Current (A)**  
 10  
**Volts (V)**  
 110-120  
**Frequency (Hz)**  
 60  
**Total annual energy consumption (kWh)**  
 253.9  
**ENERGY STAR®**  
 Yes  
**Approval certificates**  
 CSA  
**Power Cord Length**  
 118,1"  
**Required cutout size (HxWxD) (in)**  
 84" x 24" x 24 3/4"  
**Appliance Width (in)**  
 23 3/4 "  
**Height (in)**  
 83 3/4 "  
**Depth (in)**  
 24"  
**Capacity in 0.75l (bordeaux bottles)**  
**Total unit gross capacity (cu. ft.) - AHAM**  
 13.0  
**Product packaging dimensions (HxWxD) (in)**  
 89.37 x 29.52 x 27.16  
**Refrigerator Gross capacity (cu. ft.)**  
 13.0  
**Freezer Gross capacity (cu ft)**  
**Net weight (lbs)**  
 317.000  
**Gross weight (lbs)**  
 351.000  
**SKU**  
 RC462705

**Consumption and connection features**  
 2021-05-19  
 Page 1

1 fully extendable fresh cooling drawer with transparent front, illuminated.  
 Cushioned closing system.  
 Humidity can be adjusted manually.  
 Ideal for fruit and vegetables.

**Consumption data**  
 Energy consumption 253.9 kWh/year.  
 Noise level 40 dB (re 1 pW).

**Planning notes**  
 Flat hinge.  
 Door hinge right, reversible.  
 Door opening angle of 115°, fixable at 90°.  
 Max. door panel weight 90 lbs (41 kg).

**Rating**  
 Total rating 1.079 kWh/24 h.  
 Total Amps: 10 A.  
 Connecting cable 118" (3.0 m), detachable.

**Color Variants**  
**RC462705**  
**With fresh cooling 32 °F**  
**Fully integrated, panel ready**

**Included accessories**  
 1 x egg box with lid.

**Optional accessories**  
**RA430100**  
 Storage container with transparent lid, anthracite.

**Installation Accessories**  
**RA421615**  
 Stainless steel door panel with handle  
**RA423140**  
**RA425110**  
 Long stainless steel door handle  
**RA428615**  
 Stainless steel door panel, handleless  
**RA460000**  
 Installation kit for side-by-side installation (for connecting any two columns)  
**RA460012**  
**RA460020**  
 Connecting element for vertically split appliance fronts (for a flush front)  
**RA464611**  
 Ventilation grill, stainless steel

RC462705  
400 series refrigeration column  
With fresh cooling 32 °F  
Fully integrated, panel ready  
Niche width 24" (61 cm)  
2021-05-19  
Page 2

