



Color Variants

RC472705
400 series refrigeration column
With fresh cooling 32 °F
Fully integrated, panel ready

Included accessories

1 x egg box with lid.

Optional accessories

RA430100
Storage container with transparent lid, anthracite.

Installation Accessories

RA421713
Stainless steel door panel with handle
RA423140
RA425110
Long stainless steel door handle
RA428713
Stainless steel door panel, handleless
RA460000
Installation kit for side-by-side installation (for connecting any two columns)
RA460012
RA460020
Connecting element for vertically split appliance fronts (for a flush front)
RA464711
Ventilation grill, stainless steel

RC472705
400 series refrigeration column
With fresh cooling 32 °F
Fully integrated, panel ready
Niche width 30" (76.2 cm)



Stainless steel interior with solid anthracite aluminium elements
 Warm white and glare-free LED light spots
 Opening assist for door with two options:
 1. Push-to-open function for integration into handleless furniture front
 2. Pull-to-open function to facilitate opening the door using a handle
 The drawers in the RC and RF models are positioned at the same height.
 With side-by-side installation, the glass shelves and door racks can be aligned on the same level
 Flat stainless steel inner door, full-length
 Almost invisible rail system for shelves and door racks for flexible positioning
 Solid anthracite aluminium door racks
 1 fresh cooling drawer 32 °F with temperature control from 32° F to 37 °F and one fresh cooling drawer with manually adjustable humidity
 TFT touch display
 Net volume 16.8 ft³ cu.ft. (475) litres
 Energy Star certified

Operation

TFT touch display operation.
 Clear text display in 44 languages.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.
 Automatic defrosting with defrost water evaporation.
 Cushioned door closing system.
 Activated charcoal air filter.
 Sabbath mode certified by Star-K.
 When rest mode is active, the appliance can only be opened using a handle.
 Open-door and malfunction warning system.
 Home network integration for digital services (Home Connect) wireless via WiFi.
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Cooling compartment

Temperature adjustable from 35 °F to 46 °F.
 1 shallow, fully extendable drawer with transparent front.
 Cushioned closing system.
 4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.
 Flat door rail system with fully flexible positioning of door racks.
 4 height-adjustable door racks, 1 of which is extra deep.
 Net volume 406 l liters.

Fresh cooling 32 °F

1 large, fully extendable fresh cooling 32 °F drawer with transparent front, illuminated.
 Cushioned closing system.
 Temperature control via central TFT display, temperature can be adjusted from 30 °F to 38 °F.
 Ideal for meat, fish and poultry.
 Net volume 69 litres.

Temperature controlled drawer

Product Features

UPC code
 825225961079
Color / Material housing
Variant color
 Not applicable
Panel ready
 Not possible
Silence level (dBA)
 40
Watts (W)
 350
Current (A)
 10
Volts (V)
 110-120
Frequency (Hz)
 60
Total annual energy consumption (kWh)
 279.1
ENERGY STAR®
 Yes
Approval certificates
 CSA
Power Cord Length
 118,1"
Required cutout size (HxWxD) (in)
 84" x 30" x 24 3/4"
Appliance Width (in)
 29 3/4"
Height (in)
 83 3/4 "
Depth (in)
 24"
Capacity in 0.75l (bordeaux bottles)
Total unit gross capacity (cu. ft.) - AHAM
 16.8
Product packaging dimensions (HxWxD) (in)
 88.97 x 33.46 x 29.33
Refrigerator Gross capacity (cu. ft.)
 16.8
Freezer Gross capacity (cu ft)
Net weight (lbs)
 367.000
Gross weight (lbs)
 405.000
SKU
 RC472705

Consumption and connection features

2021-05-19
 Page 1

1 fully extendable fresh cooling drawer with transparent front, illuminated.
 Cushioned closing system.
 Humidity can be adjusted manually.
 Ideal for fruit and vegetables.

Consumption data

Energy consumption 279.08 kWh/year.
 Noise level 40 dB (re 1 pW).

Planning notes

Flat hinge.
 Door hinge right, reversible.
 Door opening angle of 115°, fixable at 90°.
 Max. door panel weight: 53 lbs. (24 kg).

Rating

Total rating 1.079 kWh/24 h.
 Total Amps: 10 A.
 Connecting cable 118" (3.0 m), detachable.

RC472705
 400 series refrigeration column
 With fresh cooling 32 °F
 Fully integrated, panel ready
 Niche width 30" (76.2 cm)
 2021-05-19
 Page 2

