



Color Variants

RC492705

With fresh cooling 32 °F

Fully integrated, panel ready

Included accessories

1 x egg box with lid.

Optional accessories

RA430100

Storage container with transparent lid, anthracite.

Installation Accessories

RA421914

Stainless steel door panel with handle

RA423140

RA425110

Long stainless steel door handle

RA428914

Stainless steel door panel, handleless

RA460000

Installation kit for side-by-side installation (for connecting any two columns)

RA460012

RA460020

Connecting element for vertically split appliance fronts (for a flush front)

RA464911

Ventilation grill, stainless steel

RC492705

400 series refrigeration column

With fresh cooling 32 °F

Fully integrated, panel ready

Niche width 36" (91.4 cm)



Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front

2. Pull-to-open function to facilitate opening the door using a handle

The drawers in the RC and RF models are positioned at the same height.

With side-by-side installation, the glass shelves and door racks can be aligned on the same level

Flat stainless steel inner door, full-length

Almost invisible rail system for shelves and door racks for flexible positioning

Solid anthracite aluminium door racks

1 fresh cooling drawer 32 °F with temperature control from 32° F to 37 °F and one fresh cooling drawer with manually adjustable humidity

TFT touch display

Net volume 20.6 ft³ cu.ft. (583) litres
Energy Star certified

Operation

TFT touch display operation.

Clear text display in 44 languages.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.

Automatic defrosting with defrost water evaporation.

Cushioned door closing system.

Activated charcoal air filter.

Sabbath mode certified by Star-K.

When rest mode is active, the appliance can only be opened using a handle.

Open-door and malfunction warning system.

Home network integration for digital services (Home Connect) wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Cooling compartment

Temperature adjustable from 35 °F to 46 °F.

1 shallow, fully extendable drawer with transparent front.

Cushioned closing system.

4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.

Flat door rail system with fully flexible positioning of door racks.

4 height-adjustable door racks, 1 of which is extra deep.

Net volume 498 l liters.

Fresh cooling 32 °F

1 large, fully extendable fresh cooling 32 °F drawer with transparent front, illuminated.

Cushioned closing system.

Temperature control via central TFT display, temperature can be adjusted from 30 °F to 38 °F.

Ideal for meat, fish and poultry.

Net volume 85 litres.

Temperature controlled drawer

Product Features

UPC code

825225961086

Color / Material housing

Variant color

Not applicable

Panel ready

Not possible

Silence level (dBA)

40

Watts (W)

350

Current (A)

10

Volts (V)

110-120

Frequency (Hz)

60

Total annual energy consumption (kWh)

312.2

ENERGY STAR®

Yes

Approval certificates

CSA

Power Cord Length

118,1"

Required cutout size (HxWxD) (in)

84" x 36" x 24 3/4"

Appliance Width (in)

35 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Capacity in 0.75l (bordeaux bottles)

Total unit gross capacity (cu. ft.) - AHAM

20.6

Product packaging dimensions (HxWxD) (in)

88.97 x 39.37 x 29.72

Refrigerator Gross capacity (cu. ft.)

20.6

Freezer Gross capacity (cu ft)

Net weight (lbs)

409.000

Gross weight (lbs)

451.000

SKU

RC492705

Consumption and connection features

2021-05-12

Page 1

1 fully extendable fresh cooling drawer

with transparent front, illuminated.

Cushioned closing system.

Humidity can be adjusted manually.

Ideal for fruit and vegetables.

Consumption data

Energy consumption 312.17 kWh/year.

Noise level 40 dB (re 1 pW).

Planning notes

Flat hinge.

Door hinge right, reversible.

Door opening angle of 115°, fixable at 90°.

Max. door panel weight 95 lbs. (43 kg).

Rating

Total rating 1.079 kWh/24 h.

Total Amps: 10 A.

Connecting cable 118" (3.0 m), detachable.

RC492705
400 series refrigeration column
With fresh cooling 32 °F
Fully integrated, panel ready
Niche width 36" (91.4 cm)

2021-05-12
Page 2

