SUMMIT

SWC1840B



34.25" x 17.75" x 23.5" (H x W x D)

18" wide commercial wine cellar designed for the display and refrigeration of beverages, for built-in or freestanding use with digital controls, lock, and LED lighting

Highlights:

Commercially listed to NSF-7 standards

Less than 18" wide for a perfect fit

Flexible design allows built-in or freestanding use under counters

Product Features:

34 bottle capacity	Versatile interior can store up to 34 standard 750ml Bordeaux style or wider Burgundy style bottles	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments	
Glass door with stainless steel trim	Provides a full display of stored contents with a heat-safe double tempered design	
Factory installed lock	Keyed security on the door	
Digital thermostat	Electronic controls for precise temperature management.	
Digital display	Temperature readout can be shown in Celsius or Fahrenheit	
LED lighting	Gentle illumination with an on/off switch	
Wooden shelves	5 shelves offer the perfect storage for wine bottles in a classic wooden finish	



SUMMIT

SWC1840B Specifications:

Overview		
Nominal Width	18.0" (46 cm)	
Nominal Depth	24.0" (61 cm)	
Nominal Height	35.0" (89 cm)	
Height of Cabinet	34.25" (87 cm)	
Width	17.75" (45 cm)	
Depth	23.5" (60 cm)	
Depth with door at 90°	39.75" (101 cm)	
Capacity	3.3 cu.ft. (93 L)	
Bottles	34 bottles	
Defrost Type	Automatic	
Door	Glass	
Cabinet	Black	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	1.25	
Voltage/Frequency	115 V AC/60 Hz	
Weight	95.0 lbs. (43 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101055725	
Wine Cellar		
Number of Zones	1	
Door Swing	RHD	
Reversible	Yes	
Shelf Type	Wood	
Shelf Qty	5	
Thermostat Type	Digital	
Interior Light	Yes	
Fan Type	Interior and Exterior	
Refrigerant Type	R600a	
Refrigerant Amount	1.06 oz.	
High Side PSI	150.0	
Low Side PSI	50.0	
Level Legs	4	
Temperature Range	41º to 68ºF	
Sound Level	33.8 dB	

