

BUILT-IN 42"W. SIDE-BY-SIDE

Viking 5 Series - VCSB

PROCHILL TEMPERATURE MANAGEMENT SYSTEM

- ENERGY STAR Qualified
- Variable Speed DC Overdrive[™] Compressor quickly chills food and saves energy
- Single compressor system is one of the quietest, most technologically advanced compressors available
- \bullet Electronic controls maintain even temperatures within one degree $^\circ\mathsf{F}$ to keep food fresher longer
- Odor Eliminator[™] Evaporator removes odors and excess humidity
- Maintenance-free Super Clog Resistant[™] Condenser prevents dust and other airborne particles from clogging the condenser

FILTER-FREE FRESHNESS

- EXCLUSIVE Plasmacluster[™] Ion Air Purifier uses advanced ion technology to eliminate airborne bacteria, mold, and odors to enhance food preservation
- Functions at 100% capacity and never degrades, never needs replacing, and no maintenance is ever required

LED LIGHTING

- All items are in clear view with bright energy efficient LED lighting from top and sidewalls
- Ramp on theater lighting provides better visibility

SPECIALIZED REFRIGERATION STORAGE

- One adjustable *Humidity Zone[™] Drawer* with NEW soft-close slides
 - Humidity can be set high for leafy greens or low for fruits and vegetables with skins
- Additional space for large pizza box storage
- Two deli drawers with soft-close slides
- Two in-the-door dairy compartments with covers
- Four Patented (three are adjustable) aluminum door bins securely store heavy items
- Seamless glass shelves make cleanup easy and maximize usable space
- Adjustable door stops 90, 110 and 120 degrees

SPECIALIZED FREEZER STORAGE

- Three adjustable wire shelves for custom storage
- Two slide-out, large capacity wire baskets provide easy storage viewing

ACCESSORIES

• PBIRFTKSS - Flush mount trim kit

COLOR FINISHES

Stainless Steel (SS)



- Volume 1 Color Finishes include Antique Bronze (AN), Blush (BH), Cast Black (CS), Damascus Gray (DG), Eucalyptus (EU), Ivy (IV), Martini (MA), November Sky (NS), Slate Blue (SB), Spiced Cider (SC), Splash (SP)
- Volume 2 Color Finishes include Daffodil (DA), Golden Hour (GH), Nantucket (NA), Onyx (ON), Pure White (PW), Squall (SQ), Valentine (VA)





- Three patented adjustable aluminum door bins
- Adaptive defrost controls the timing of the defrost periods, instead of an electromechanical defrost timer
 - Extends to 96 hours improves food storage because the unit defrosts less often
- Factory-installed automatic ice maker features *large-capacity* ice bucket
- Door alarm sounds and glows to warn that fresh food door and/ or freezer drawer have been ajar for three minutes, and that the temperature has risen above normal operating range

MODEL NUMBERS

VCSB5424 – 42"W. Side-by-Side Refrigerator/Freezer

WARRANTY

- 2-year full covers complete unit
- 6-year full sealed refrigeration system
- 90-day full cosmetic parts such as glass, painted items, and decorative items
- 12-year limited sealed refrigeration system




BUILT-IN 42"W. SIDE-BY-SIDE

Viking 5 Series – VCSB

42"W. SIDE-BY-SIDE		
DESCRIPTION	VCSB5424	VCSB5424 FLUSH MOUNT
Overall Width	42" (106.7 cm)	
Overall Height (from bottom)	82-3/4" (210.2 cm) min. to 84-1/16" (213.5 cm) max.	
Overall Depth from rear To front edge of side trim: To front of top grille: To front of handle endcap:	23-3/4" (60.3 cm) 26-1/4" (66.7 cm) 29-3/16" (74.1 cm)	25-1/2" (64.8 cm) 26-1/4" (66.7 cm) 29-3/16" (74.1 cm)
Cutout Width	41-5/8" (105.7 cm) min. to 41-3/4" (106 cm) max.	42" (106.7 cm)
Cutout Height	82-7/8" (210.5 cm) min. to 84-1/16" (213.5 cm) max.	
Cutout Depth	24" (61.0 cm) min.	26-1/2" (67.3 cm) min.
Electrical Requirements	115 volt, 60 Hz, 15 amp dedicated circuit; 3-wire cord with grounded 3-prong plug attached to product	
Maximum Amp Usage	9.9 amps	
Inlet Water Requirements	1/4" copper tubing inlet waterline; min. 20 psi; max. 120 psi	
Overall Interior Dimensions Refrigerator Freezer Total Capacity	15.76 cu. ft. (446 liters) 9.56 cu. ft. (271 liters) 25.32 cu. ft. (717 liters)	15.76 cu. ft. (446 liters) 9.56 cu. ft. (271 liters) 25.32 cu. ft. (717 liters)
Approximate Shipping Weight	525 lb. (238 kg)	525 lb. (238 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com © 2023 Viking Range, LLC All rights reserved. Specifications subject to change without notice.