



VI 230 620

Black control panel
Width 12" (28 cm)

Included accessories

1 glass scraper

Installation accessories

VV 200 010

Stainless steel connection strip for combination with other Vario appliances of the 200 series

VV 200 020

Black connection strip for combination with other Vario appliances of the 200 series

Optional accessories

GP 900 001

Stainless steel frying sensor pan
Non-stick cooking, ø 6".

GP 900 002

Stainless steel frying sensor pan
Non-stick coating, ø 7".

GP 900 003

Stainless steel frying sensor pan
Non-stick coating, ø 8".

VD 200 020

Black appliance cover

Combinable with:

VL200120
AI442720 / AI442760
AW442720 / AW442760
AI230700
AW230790
AF210791 / AF210761

Good to know:

Wall installations require the hood to be as large as the cooktop(s). Island installations require the hood to be larger than the cooktop(s).

Vario 200 series induction cooktop

VI 230

- Can be combined with other Vario 200 series products
- Control panel for comfortable and secure operation

Cooking zones

1 induction cooking zone 9" (2,200 W, with booster 3,700 W)
1 induction cooking zone 6" (1,400 W, with booster 1,800 W)

Operation

Control knobs with illuminated ring.
Integrated control panel.
Electronic power control in 9 output levels.

Features

Cooking area marking.
Frying sensor function.
Pot detection.
Booster function for both cooking zones.

Safety

Residual heat indication.
Operation indicator.
Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of flat bottom cookware is recommended.
To insure that the appliance works correctly, the cooktop must be sufficiently ventilated either from the rear or base of the cabinet.
Appliance can be snapped into the countertop from above.
Appliance weight: approx. 15.4 lbs (7kg).

Rating

Rating: 3,700 W
Minimum fuse protection: 15 A
Electrical: 208 / 220-240 V / 60 Hz
Electrical connection:
Hardwire required, 37" cable length.

