

## **5 SERIES 36"W. INDUCTION RANGE**

Viking 5 Series - VIR

#### COMMERCIAL-TYPE COOKING POWER

- MagneQuick™ Induction Power Generators utilize magnetic energy for superior power, responsiveness, and efficiency
- Power management induction system provides a boost of superior power on all elements for faster boil times
- Large 9" induction elements each provide up to 3,700 watts of power
  - Six large 9" 3,700–2,300-watt induction elements
- Simmer setting is perfect for gentle melting or keeping cooked food warm
- Heavy-duty BlackChrome<sup>™</sup> knobs and square bezels shipped standard
- One of the largest oven cavities in the industry
- EXCLUSIVE patented Vari-Speed Dual Flow™ Convection
   System has the largest convection fan in the industry; the 8-1/2" fan works bi-directionally for maximum airflow and excellent cooking results
- Concealed 10-pass dual bake element provides precise temperature control
- Large 10-pass broiler with heat reflector
- Rapid Ready<sup>™</sup> Preheat provides one of the fastest preheat times, meaning less wait time for the oven to preheat
- Oven has six porcelain-coated rack positions and comes standard with three oven racks
- **EXCLUSIVE** Gentle Close<sup>™</sup> Door allows door to close slowly
- Three strategically located oven lights provide maximum visibility
- High-performance cooking modes include bake, convection bake, TruConvec convection cooking, convection roast, broil, convection broil, convection dehydrate, and convection defrost



### **EASY OPERATION AND CLEANUP**

- NEW surface graphics on strong, wear-resistant glass ceramic surface for excellent cleanability
- Self-cleaning porcelain oven
- Concealed 10-pass dual bake element makes for easy cleanup of the oven cavity

#### **MODEL NUMBER**

■ VIR53626B - 36"W. Induction Range; six elements

#### **ACCESSORIES**

- BG8536SS 8"H. backguard for 36" range
- HS24536SS high shelf for 36" range
- P24CSTSS countertop side trim (2 pieces)
- P36CRTSS countertop rear trim for 36" range
- P36CBF4SS curb base and custom curb base front for 36" range

#### **COLOR FINISHES**

Stainless Steel (SS)



 Volume 1 Color Finishes include Antique Bronze (AN), Blush (BH), Cast Black (CS), Damascus Gray (DG), Eucalyptus (EU), Ivy (IV), Martini (MA), November Sky (NS), Slate Blue (SB), Spiced Cider (SC), Splash (SP)



 Volume 2 Color Finishes include Daffodil (DA), Golden Hour (GH), Nantucket (NA), Onyx (ON), Pure White (PW), Squall (SQ), Valentine (VA)

#### **WARRANTY**

- 2-year full complete product
- 90-day full cosmetic parts such as glass, painted items and decorative items
- 5-year limited induction element components



# **5 SERIES 36"W. INDUCTION RANGE**


Viking 5 Series - VIR

36"W. INDUCTION RANGE	
DESCRIPTION	VIR53626B
Overall Width	35-7/8" (91.1 cm)
Overall Height from Bottom	Base Height To top of glass frame — minimum 35-7/8" (911 cm) to maximum 37" (94 cm); legs adjust 1-1/8" (2.9 cm) Additions to Base Height To top of island trim — add 1" (2.5 cm); to top of backguard — add 8" (20.3 cm) To top of high shelf — add 24" (61.0 cm)
Overall Depth from Rear	To end of side panel — 24-7/8" (63.2) To front of door — 26-1/8" (66.4 cm) To end of door handle — 28-3/4" (73 cm)
Electrical Requirements	240-208VAC, 60 Hz electrical connection box on product, connect with locally supplied 3-wire, flexible cord or "pigtail" rated 50 amp 125-250VAC minimum. Cord must be agency approved for use with household electric ranges.
Circuit Breaker	50 amp dedicated circuit
Surface Burner/Element Rating	Left Front: 3,700-watt boost/2,300 watts Left Rear: 3,700-watt boost/2,300 watts Center Front: 3,700-watt boost/2,300 watts Center Rear 3,700-watt boost/2,300 watts Right Front: 3,700-watt boost/2,300 watts Right Rear: 3,700-watt boost/2,300 watts
Oven Interior Dimensions	Overall Width — 30-5/16" (76.9 cm)  Height — 16-1/2" (41.9 cm)  Depth — 19-1/2" (49.5 cm)  Overall Size — 5.6 cu. ft.  AHAM Standard" — 4.9 cu. ft.  3 racks, 6 rack positions
Approximate Shipping Weight	525 lb. (193,2 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.

\*\*The AHAM Standard for measuring oven capacity subtracts the door plug and convection baffle dimension from the total oven volume.

208V ratings – Time required for some functions may be extended due to less wattage.





VIKING RANGE, LLC 111 FRONT STREET GREENWOOD, MISSISSIPPI 38930 USA

c Users User

For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com © 2024 Viking Range, LLC All rights reserved. Specifications subject to change without notice.

F60446B